

Driving in extreme condition calls for a trusted companion to generate a powerful start. Presenting the Tandhan Power range of battery systems from the most trusted power storage solution provider in India. An wide array of passenger and commercial vehicle batteries have been engineered to excel even on rough roads and challenging climate parameters. The time tested experience of manufacturing international quality products make Tandhan Power batteries an obvious choice for global driving community.

Lid mounted window indicator is provided, which changes color when electrolyte falls below specified level for immediate top-up and hence ensure longer life.

ELECTROLYTE LEVEL INDICATOR

ADVANCED TECHNOLOGY SEPARATORS

To add high reliability and reduce resistance, improved separators are used.

HIGH PERFORMANCE PLATES

Electrolyte spilling is resisted in Tandhan Power batteries with introduction of leak and explosion proof venting system, to ensure greater safety even while driving on rough roads.

SAFETY VENTING

Manufactured with advanced alloy, Tandhan Power battery plates are designed to reduce grid passivation. Specially designed plates with superior tensile strength, high temperature creep resistance and longer charge holding capacity add greater endurance to Tandhan Power batteries.

EASY HANDLING

Ergonomic yet strongly reinforced light weight polypropylene case with convenient lifting handle design ensures great maneuverability to Tandhan Power batteries.


INEXHAUSTIBLE POWERHOUSE

Tandhan Power range for passenger car, utility vehicles and light commercial vehicles

| | To the latest the late | | Ampere-hour | Cold cranking | Reserve | Dim | ensions (m | ım) | Charge |
|--------------|--|-----|---------------------------|-------------------------------|--|-----|------------|--------|-----------|
| Nomenclature | Lay | out | capacity at C20 rating | performance (Amps) SAE/EN1 | The Control of the Co | | Width | Height | Indicator |
| 38B19 | L,0 | R,1 | 35 | 272 | 43 | 187 | 127 | 227 | * |
| 44B20-BH | L,0 | R,1 | 35 | 272 | 49 | 197 | 127 | 227 | ~ |
| 40B24 | L,0 | R,1 | 40 | 225 | 51 | 238 | 129 | 227 | ~ |
| 40B24-S | L,O | R,1 | 40 | 225 | 51 | 238 | 129 | 227 | 4 |
| 60B24 | L,0 | R,1 | 45 | 369 | 64 | 238 | 129 | 227 | - |
| 60B24-S | L,O | R,1 | 45 | 369 | 64 | 238 | 129 | 227 | ~ |
| 55D23-BH | L,0 | R,1 | 60 | 460 | 90 | 232 | 172 | 255 | ~ |
| 75D23-BH | L,0 | R,1 | 62 | 500 | 100 | 232 | 172 | 255 | ~ |
| 48D26-BH | L,0 | R,1 | 50 | 340 | 72 | 260 | 173 | 225 | ~ |
| 55D26-BH | L,O | R,1 | 60 | 460 | 90 | 260 | 173 | 225 | 1 |
| 65D26-BH | L,0 | R,1 | 65 | 500 | 100 | 260 | 173 | 225 | * |
| 80D26-BH | L,0 | R,1 | 70 | 540 | 110 | 260 | 173 | 225 | ✓. |
| 65D31-BH | L,0 | R,1 | 70 | 520 | 110 | 305 | 173 | 225 | 4 |
| 75D31-BH | L,0 | R,1 | 75 | 560 | 120 | 305 | 173 | 225 | 1 |
| 95D31-BH | L,0 | R,1 | 80 | 600 | 130 | 305 | 173 | 225 | 4 |
| 105D31-BH | L,0 | R,1 | 90 | 720 | 150 | 305 | 173 | 225 | - |
| 115D31-BH | L,0 | R,1 | 95 | 750 | 155 | 305 | 173 | 225 | ~ |
| DIN43-LH | L,0 | NA | 43 | 324 | 57 | 210 | 175 | 175 | ~ |
| DIN44 | L,0 | R,1 | 44 | 360 | 62 | 210 | 175 | 190 | ~ |
| DIN50 | L,O | R,1 | 50 | 405 | 71 | 210 | 175 | 190 | * |
| DIN55 | L,0 | R,1 | 55 | 420 | 80 | 243 | 175 | 190 | 4 |
| DIN60 | L,O | R,1 | 60 | 440 | 88 | 243 | 175 | 190 | · · |
| DIN62 | L,0 | R,1 | 62 | 480 | 90 | 243 | 175 | 190 | ~ |
| DIN66 | L,O | R,1 | 66 | 480 | 110 | 278 | 175 | 190 | * |
| DIN72-LH | L,0 | R,1 | 72 | 585 | 100 | 278 | 175 | 175 | ~ |
| DIN74 | L,0 | R,1 | 74 | 570 | 115 | 278 | 175 | 190 | 1 |
| DIN80 | L,0 | NA | 80 | 675 | 141 | 313 | 175 | 190 | (m) |
| DIN90 | L,0 | NA | 90 | 720 | 144 | 353 | 175 | 190 | ((4) |
| DIN100 | L,0 | NA | 100 | 720 | 141 | 353 | 175 | 190 | - |

Tandhan Power range for heavy commercial vehicles

| Nomenclature | Layout | | Ampere-hour | Cold cranking | Reserve | Dimensions (mm) | | | | Charge |
|----------------|--------|-----|---------------------------|----------------------------|-----------|-----------------|-------|--------|--------|-----------|
| | | | capacity at C20 rating | performance (Amps) SAE/EN1 | (Minutes) | Length | Width | Height | Handle | Indicator |
| MF100 (95E41) | L,0 | R,1 | 100 | 576 | 163 | 410 | 176 | 233 | Yes | * |
| MF120 (115F51) | L,3 | R,4 | 120 | 612 | 205 | 505 | 182 | 240 | Rope | 24 |
| MF150 (145G51) | L,3 | R,4 | 150 | 706 | 264 | 508 | 222 | 257 | Rope | - |
| MF170 | L,3 | R,4 | 170 | 706 | 264 | 508 | 222 | 240 | Rope | - |
| MF200 (195H52) | L,3 | R,4 | 200 | 950 | 330 | 521 | 278 | 242 | Rope | - |
| DIN170 (67018) | L,3 | NA | 170 | 940 | 340 | 513 | 223 | 215 | Rope | ~ |
| DIN180 (68032) | L,3 | NA | 180 | 850 | 320 | 513 | 223 | 215 | Rope | 4 |



TERMINAL DETAILS

| 4 | Types of | Tip diameter (f.D) | | | | |
|-------------|-----------|--------------------|---------------|--|--|--|
| -((;))- | terminals | Positive (mm) | Negative (mm) | | | |
| Fuel 1 1,+3 | T1 | 14.7 0 -0.3 | 13.0 0 | | | |
| D V | T2 | 19.5 0 | 17.9 0 | | | |

Conform to JIS 5301-1999 and DIN standards. All Tandhan Power batteries are fitted with charge indicator (acid level indicator) and supplied in black container. No charge indicator for DIN90. *Supplied in white container and black lid

Tandhan Power is a brand owned by

Tandhan Impex Private Limited

103 PARK STREET, KOLKATA - 700016

For more details please visit www.tandhanpower.com

EFB START STOP "WE BELIEVE IN TECHNOLOGY BREAK THROUGHS"

Tandhan Power range for passenger car, utility vehicles and light commercial vehicles

| Nomenclature | | | Ampere- | | Dimension | ns (mm) | | Lamenton. | |
|--------------|-----|--------|---------|-----|-----------|---------|--------|-----------|-------------|
| | | Layout | hour | CCA | Length | Width | Height | Handle | Terminal |
| EFB-M42-B20 | L,0 | R,1 | 38 | 340 | 197 | 127 | 227 | Υ | SMALL |
| EFB-N55-B24 | L,0 | R,1 | 50 | 430 | 238 | 129 | 227 | Υ | SMALL & STD |
| EFB-Q85-D23 | L,0 | R,1 | 65 | 550 | 232 | 172 | 225 | Υ | STANDARD |
| EFB-S95-D26 | L,0 | R,1 | 75 | 680 | 260 | 173 | 225 | Υ | STANDARD |
| EFB-T110-D31 | L,0 | R,1 | 90 | 740 | 305 | 173 | 225 | Υ | STANDARD |
| EFB-L1- | L,0 | R,1 | 50 | 430 | 207 | 175 | 190 | Υ | STANDARD |
| EFB-L2 | L,0 | R,1 | 60 | 500 | 243 | 175 | 190 | Υ | STANDARD |
| EFB-L3 | L,0 | R,1 | 74 | 600 | 278 | 175 | 190 | Y | STANDARD |
| EFB-L4 | L,0 | NA | 80 | 750 | 313 | 175 | 190 | Υ | STANDARD |
| EFB-L5 | L,0 | NA | 100 | 800 | 353 | 175 | 190 | Y | STANDARD |

Tandhan Power range for heavy commercial vehicle

| Nomenclature | 700000 | | Ampere- | 31215 | Dim | ensions (m | NAME OF THE PARTY OF | -52/1/2001/WI | |
|-----------------|--------|--------|---------|-------|--------|------------|----------------------|---------------|----------|
| | | Layout | hour | CCA | Length | Width | Height | Handle | Terminal |
| EFB-E41-MF100 | L,0 | R,1 | 100 | 680 | 410 | 176 | 233 | M.EYE/HANDL | STANDARD |
| EFB-F51-MF120 | L,3 | R,4 | 120 | 780 | 505 | 182 | 240 | Rope | STANDARD |
| EFB-DINB -MF150 | L,3 | R,4 | 150 | 850 | 513 | 224 | 220 | M.EYE/ROPE | STANDARD |
| EFB-DINB-MF170 | L,3 | R,4 | 170 | 900 | 513 | 224 | 220 | M.EYE/ROPE | STANDARD |
| EFB-DINC-MF200 | L,3 | R,4 | 200 | 1050 | 514 | 275 | 242 | M.EYE/ROPE | STANDARD |
| EFB-DINC-MF225 | L,3 | R,4 | 225 | 1150 | 514 | 275 | 242 | M.EYE/ROPE | STANDARD |

Tandhan Power is a brand owned by

Tandhan Impex Private Limited

103 PARK STREET, KOLKATA - 700016

For more details please visit www.tandhanpower.com